

MANUAL SECTION	ISSUE DATE	AUTHORISED	REPLACES	PAGE
Roofing	August 1999	RIC	October 1997	1 of 2

SOPREMA MEMBRANES

GENERIC TYPE:

A range of APP and SBS modified hot torch applied bituminous waterproofing sheet membranes.

TYPICAL PROPERTIES:

- Prefinished surface - finishes available - copper, aluminium, stainless steel, coloured slate chippings.
- Guaranteed
- Available un-finished for tanking or first layer of double layer system.
- Plain sand finished suitable on roofs and gutters if overcoated with **CURAL** aluminium finish.
- SBS or APP modified.
- Torch on.
- Reinforced with non-woven polyester to resist puncturing and tearing.
- Remains flexible in cold temperatures.
- Will adhere to most substrates.
- Single or double layer systems.
- Elastic properties - allow membrane to stretch and return to original shape.

SUGGESTED USES:

- Waterproofing flat and low pitched roofs
- Balconies and terraces
- Carports and bridges
- Below ground tanking
- Under tiles
- Gutters

NOT RECOMMENDED

- Exposure to UV without protection (i.e. granule or metal versions).
- Areas subject to chemical attack without consulting Nuplex Industries re suitability.
- Application to incorrectly prepared or unsound substrates.

No warranty either expressed or implied or statutory is made by NUPLEX in this document except as expressly stated in any sale and purchase agreement entered into between NUPLEX and the buyer.

This document is a technical data information sheet. The description of the product or products and the properties of the product or products contained in this document is for the sole purpose of identifying the product or products and describing their property or properties and does not constitute a warranty that the product or its properties shall conform to that description; nor is the description of the product and/or its properties a warranty by NUPLEX that the goods are suitable for a particular purpose.

NUPLEX CONSTRUCTION PRODUCTS

PO Box 12841, Penrose, Auckland Telephone 0-9-579 2029 Fax 0-9-525 3709 www.nuplexbuilding.co.nz email: bpdsales@nuplex.co.nz

H A M I L T O N	P A L M E R S T O N N O R T H	W E L L I N G T O N	C H R I S T C H U R C H
Telephone 0-7-847 8658	Telephone 0-6-353 3685	Telephone 0-4-499 1341	Telephone 0-3-366 6802
Fax 0-7-847 3766	Fax 0-6-353 3632	Fax 0-4-471 5709	Fax 0-3-365 7845

SOPREMA MEMBRANES (cont'd)

Application to an unprimed substrate.

Application to a trafficable deck (foot or vehicular) unless protected (eg: tiles, concrete).

Mixing of APP and SBS systems without consulting Nuplex.

SELECTION CHART: Attached

DETAILING: Refer Nuplex Industries for full detail drawings.

NUMBER OF LAYERS: 1 or 2 depending on requirements.

APPLICATION:

Primer:	Roller/brush
	Coverage 5m ² /litre
Membrane	Hot torch

SUBSTRATE AND INSTALLATION: Refer specification sheet.

PRIMER:

Clean Up: Universal Cleaning Solvent

Hazchem: 3(Y)E

UN No.: 1133
(Refer Membrane Primer data sheet)

SOPREMA MEMBRANES AS HORIZONTAL TANKING:

Soprasun 3 and Soprasun 4 are used as torch-on tanking for horizontal surfaces. Specify single or double layer application as required for adequate structure protection. Pavers or tiles may be loose laid or directly bonded using Nuplex **RED LABEL** adhesive (refer data sheet).

PLAIN FINISHES:
(on roofs and gutters)

EG: SOPRASUN 4
These may be left exposed if overcoated with Cural Aluminium paint (400gsm).

PRODUCER STATEMENT

Soprema membranes supplied by Nuplex Industries Ltd are stated to comply with the Building and all requirements of the Building Industry Authority.