

MANUAL SECTION	ISSUE DATE	AUTHORISED	REPLACES	PAGE
----------------	------------	------------	----------	------

<i>Flooring</i>	<i>Dec 2010</i>	<i>PM</i>	<i>Jan 2010</i>	<i>1 page</i>
-----------------	-----------------	-----------	-----------------	---------------

Intafloors Plywood Underlayment

Product specification

Specifically manufactured flooring reinforcement system

Sheet size: 1.22m x 1.22m x 5.2mm
 Durable 5 ply construction
 Durable, stable & stiff flooring underlayment.
 Moisture content: <12%
 Both sides sanded.
 Fixing marks on top surface
 Tolerances:
 Squareness, length and width ± 1.0mm
 Thickness = ± 0.15mm
 Formaldehyde grade = E0 less than 0.5mg/l



Packaging – 78 sheets per pallet, 13 x 6 packets . The ply's are solid and guaranteed to be free of voids. Guaranteed not to warp or delaminate.

INSTALLATION

Stapled (9120) (20mm leg), screwed or nailed. It may be glued if required.

Cutting

Easy to cut and lay. Fixing positions marked. Double-Score front and back with knife then snap.

Plywood sheets create a very strong timber floor underlayment. It is stronger and more reinforcing than composite timber boards.

There is less thermal and moisture distortion over time. (MF ply adhesive passes boiling water test). The ability to reinforce weak timber floors is far greater with this product.

Staple and screw head may be "buried" into the ply without sheet distortion (as distinct to composite boards). Plywood creates an ideal base for adhesives for vinyl sheet, carpet or tile.



From This



To This