

Nuplex Quartzzite

Decorative Stone Flooring



E-MAIL: bpdsales@nuplex.co.nz
WEBSITE: www.nuplexbuilding.co.nz

THE INDUSTRY LEADERS IN
SPECIALIST FINISHES & SYSTEMS SINCE 1956

CERTIFIED ISO 9001

REG NO. 158

AUCKLAND

721 Great South Road
Penrose Auckland
New Zealand P.O.Box 12-841
Telephone (09) 579-2029
Fax (09) 525-3709

HAMILTON

18 Somerset St
PO Box 1455
Telephone: (07) 847-8658
Fax: (07) 847-3766

PALMERSTON NORTH

216 John F Kennedy Drive
Palmerston North
New Zealand P.O.Box 1262
Telephone (06) 353-3685
Fax (06) 353-3632

WELLINGTON

Unit 1, 6 Hurring Place
Newlands
New Zealand P.O. Box 4008
Telephone (04) 477-7040
Fax (04) 477-7039

CHRISTCHURCH

14 Iversen Terrace
Christchurch
New Zealand P.O. Box 7501
Telephone (03) 366-6802
Fax (03) 365-7845



NUPLEX QUARTZZITE

Decorative, Stone floor Finish

PURPOSE

An insitu applied, very attractive, coloured, natural quartz stone finish for use in commercial, retail and residential premises where appearance, durability and low maintenance are important.

PROPERTIES

- Solvent free
- Natural Quartz aggregate
- Slight textured finish
- Seamless
- Standard and custom colours
- Custom designs
- No on-site grinding
- Versatile
- Light weight
- Thin application
- Low odour during installation
- Hard wearing
- Safe slip resistant finish
- Low in-service maintenance cost
- Limitless design opportunities
- Create patterns, logos and designs
- Quick installation, minimal disruption
- Use on new and refurbishment projects
- 8-10kgs m²
- 4-5mm easy use with other floor coverings

RECOMMENDED USES

Interior/exterior where appearance, durability and low maintenance are important:

Entry foyers Showrooms Shops Bars Supermarkets
Hospitals Fire stations Prisons Pharmaceutical Restaurants

Including residential, retail, commercial and light industrial areas. Can be applied to coves and skirtings.

COLOURS/DESIGN

- Refer to colour chart.
- Custom colours can be created by blending available coloured quartz stones.
- Design patterns, logos, divisions of colour and pattern using metal angle strips or temporary formwork.

APPLICATION METHOD

Nuplex Quartzzite is a trowel applied specialist floor finish and is only available from fully trained licensed Nuplex Contractors. Contact details of your local contractor can be obtained from your local Nuplex Construction Products branch.

LIMITATIONS

- Not recommended for heavy duty industrial or food processing environments.
- Substrates must be suitable, stable and sound - refer to Nuplex specification 478.
- Use of concrete cure or release agents without Nuplex approval.
- Over ceramic tiles without specific, written Nuplex design specification.
- Unsuitable for green concrete.

MAINTENANCE AND CARE

- Nuplex Quartzzite requires no special maintenance or care. Vacuum or wipe with a damp cloth or mop and detergent.
- Soiled surfaces can be cleaned using a neutral solvent-based detergent and light brushing.
Finish using wet vacuum or mop.
- Surfaces may be sealed and polished using approved materials or left untreated.
Untreated, heavy wear areas may require surface sealing at approximately 5 year intervals.

FOR FURTHER INSTRUCTIONS

Refer to Nuplex Specification 478 and Technical Data sheet "Nuplex Quartzzite"

AUCKLAND

721 Great South Road
Penrose Auckland
New Zealand P.O.Box 12-841
Telephone (09) 579-2029
Fax (09) 525-3709

HAMILTON

18 Somerset St
PO Box 1455
Telephone: (07) 847-8658
Fax: (07) 847-3766

PALMERSTON NORTH

216 John F Kennedy Drive
Palmerston North
New Zealand P.O.Box 1262
Telephone (06) 353-3685
Fax (06) 353-3632

WELLINGTON

Unit 1, 6 Hurring Place
Newlands
New Zealand P.O. Box 4008
Telephone (04) 477-7040
Fax (04) 477-7039

CHRISTCHURCH

14 Iversen Terrace
Christchurch
New Zealand P.O. Box 7501
Telephone (03) 366-6802
Fax (03) 365-7845

