


# TRUESTIK VA1

Adhesive for PVC vinyl sheet flooring



TRUESTIK  
FLOORING  
ADHESIVES

## Uses:

Truestik VA1 is a high quality waterbased acrylic adhesive used to bond sheet vinyl flooring and vinyl backed products. It has high bond strength, good tack build-up to aid the contractor in the laying process. Suitable for:

- ◆ PVC sheet flooring materials
- ◆ PVC backed carpets
- ◆ Vinyl tiles: VCT, HPL, VET
- ◆ Wall vinyl
- ◆ Vinyl laminates

## Surface Preparation:

Truestik VA1 is suitable for use on concrete and composite timber materials (plywood, particle board etc).

**Strip t&g timber flooring:** Overlay with Masonite, stapled (and preferably glued).

**Concrete:** Ensure the concrete is smooth, clean and dry.

Rough or uneven floors may be smoothed or levelled with Durabond FLC, Superset, NC160, Matrix. Refer to these datasheets separately. These products are variably trowel applied or self levelling, fast set or high build-up.

Wet floors should be left to dry. Damp floors may be treated with Aquaguard 101. Apply levelling compounds over Aquaguard 101, not visa versa.

**Particle board and Plywood.** Sand these surfaces smooth ensuring the nails will not contact the floorcovering. There are wide variations in porosity of these products due to the degree of weathering that has occurred during construction. Weathered and sanded particle board is very porous. Sealing with Duraseal is recommended. This will ensure that the adhesive will not be absorbed into porous particle board. It will also ensure the adhesive does not set up too quickly.

## Application:

Once the substrate is prepared cut the vinyl to fit as required. Truestik VA1 is applied with a notched trowel. Nuplex recommend a fine V-notched trowel (680 ACT)(STV!) or, depending on the smoothness of the flooring or the vinyl backing use a fine-medium notch (RCA)(STV2).

Apply the adhesive in an even pattern across the floor. Lay the floorcovering into the adhesive while it is all still wet. Roll with a speciality floor roller to ensure full contact between the adhesive and floorcovering. Do not allow the adhesive to set prior to laying the sheet into the vinyl and rolling it to form a continuous bond.

Allow the adhesive to dry before attempting vinyl seam welding.

Close the pail lid tightly after use.

## Features:

Tough flexible bond.

Easy to carry 15lt pail

Shelf life 12months in unopened pails

Storage in cool interior areas.

See panel on the right.

**Apply online for a Nuplex certificate in Low VOC, solvent free adhesives.**

Limitations:

Acrylic adhesives have medium heat resistance. Vertical applications in very warm environments may cause problems.

Acrylic adhesives will resist the normal dampness in concrete but are not waterproof.



Disclaimer: This adhesive is designed for use with commonly available materials. It is the users responsibility to ensure that this adhesive is suitable for use with the particular product being bonded. We suggest trial areas are applied. Advise Nuplex immediately of any issues relating to the use of the product with specific floorcoverings and do not proceed until satisfied

August 2008

## Technical Datasheet

### Key Features

- ◆ Vinyl flooring adhesive
- ◆ Strong & early tack development
- ◆ Extremely strong & permanent bond.
- ◆ Guaranteed for all commonly used vinyls and vinyl backed flooring products.
- ◆ Full plasticiser resistance
- ◆ Zero solvent content  
VOC free material  
Suitable for use in enclosed workspaces. Use of the adhesive will not effect public or others working in the environment.

**ZV solvent FREE.** (ZV refers to Zero VOC (volatile organic content)).

**MULTIPURPOSE** adhesive for many applications

Other TRUESTIK products:

Truestik CA1 Carpet

Truestik CA2 Carpet PS

Truestik EA Epoxy Adhesive

Truestik CTA Carpet Tile adhesive

*The Truestik range is formulated to have zero chemical emission to assist both the installer & others in the workplace.*

Phone: 0508-882288

Email: [ncpsales@nuplex.co.nz](mailto:ncpsales@nuplex.co.nz)  
[www.nuplexconstruction.co.nz](http://www.nuplexconstruction.co.nz)

**nuplex**

Construction Products