

DESCRIPTION

SOPRAVAP'R is a self-adhesive membrane composed of SBS modified bitumen and a tri-laminated woven polyethylene facer. The underface is covered with a silicone release film.

SOPRAVAP'R is used as a vapour barrier on insulated roof systems.

The width of the membrane has been specifically determined to allow the membrane to fit with most structural steel decks.

RECOMMENDED SUBSTRATES

SOPRAVAP'R can be installed on most substrates, such as steel, concrete, plywood, gypsum or cement boards, and asphaltic panels.

SURFACE PREPARATION

Except for the steel deck, all substrates must be primed with **ELASTOCOL STICK** or **ELASTOCOL STICK ZERO**. The substrate should be clean and sound, free of loose materials or contaminants, such as water and grease which may compromise the performance of the product.

APPLICATION

SELF-ADHESIVE

SOPRAVAP'R is adhered to substrate by peeling off the silicone release film.

Side laps must be a minimum of 75 mm (3 in) and end laps must be a minimum of 150 mm (6 in). All end laps on steel deck shall be supported by a metal plate 15 cm x 106 cm (6 in x 42 in).

Once installed, pressure must be applied over the whole surface using a roller to ensure a perfect adhesion. Minimum application temperature: - 10 °C (14 °F)

FOR COMPLETE INFORMATION ON PRODUCT INSTALLATION, PLEASE CONSULT YOUR ALLNEX REPRESENTATIVE.

PROPERTIES

Properties	SOPRAVAP'R
Thickness	0.8 mm (31 mil)
Dimensions	40.8 x 1.14 m (134 x 3.7 ft)
Gross / Net coverage per roll	46.5 / 43.5 m ² (500 / 468 ft ²)
Weight	0.77 kg/m ² (0.16 lb/ft ²)
Selvedge width	75 mm (3 in)
Top face	Tri-laminate woven polyethylene
Underface	Silicone release film
Rolls per skid	25

(All values are nominal)

PRECAUTIONS

If **SOPRAVAP'R** is not immediately covered, particular attention should be paid to implementation of details to ensure a perfect temporary seal.

All «T» joints and transitions (90 °) should be covered with **SOPRAMASTIC** sealant. If fishmouths or other openings are created to overlap, they must be sealed with **SOPRAMASTIC** sealant.

PROPERTIES

Properties	Standards	SOPRAVAP'R
Tensile strength, MD/XD	ASTM D5147	9.5 / 13 kN/m (54 / 74 lbf/in)
Ultimate elongation, MD/XD	ASTM D5147	33 / 25 %
Cold bending	ASTM D5147	- 50 °C (- 58 °F)
Static puncture	ASTM D5602	400 N (90 lbf)
Tear resistance, MD/XD	ASTM D1970	423 / 458 N (95 / 103 lbf)
Lap adhesion	ASTM D1876	1000 N/m (68 lbf/ft)
Water absorption	ASTM D5147	0.1 % max.
Peel resistance on steel	ASTM D903	950 N/m (5.4 lbf/in)
Water vapour permeance	ASTM E96 (Procedure B)	1.7 ng/Pa.s.m ² (0.03 perm)
Air permeability	ASTM E2178	< 0.001 L/s.m ²

SOPRAVAP'R membrane is evaluated in accordance with the requirements contained in CAN/ULC-S126, *Standard Method of Test for Fire Spread Under Roof Deck Assemblies*.

(All values are nominal)

STORAGE & HANDLING

Rolls must be stored upright. If the product is stored outdoors, cover them with an opaque protective cover after removal of the delivery packaging.

Date: July 2018

Replaces: New



Allnex Construction Products, a Division of Allnex New Zealand Ltd

Auckland - 14 Industry Road Penrose phone: 095836544. Hamilton - 18 Somerset Street Frankton phone: 07-847-8658

Wellington - 19A Jamaica Drive Grenada North phone: 04-240-0305. Christchurch - 112 Carlyle Street Sydenham phone: 03-366-6802

Customer Service: 0508-882-288 cs.constructionnz@allnex.com

www.allnexconstruction.com

DISCLAIMER: This information appearing in this Document (**Details**) concerning the product which is the subject of the Document (**Product**) is either based on present technical knowledge and tests done by allnex or tests done by, and data supplied from third parties including you, the customer. Since the actual use by you and by others of the Product is beyond the control of allnex, no warranty or representation, express or implied is made by allnex regarding the suitability for such use, nor does allnex accept any liability arising out of the use by you of other products or materials, whether third party or not, that may be referred to in this Document. allnex recommends that you carry out your own tests as to the suitability of the Product for your purpose, regarding which you accept full responsibility. In addition, if any of the Details appearing in the Document are based upon tests done by, and/or data supplied by any third party, allnex provides no warranties or representations in connection with those Details and you, the customer waives any right you may have against allnex in connection with the accuracy, completeness or otherwise of the Details. The information in this Document is not to be construed as absolutely complete or accurate since additional information may be necessary or desirable when particular or exceptional conditions or circumstances exist or because of applicable laws or government regulations affecting use of the Product. allnex does not provide any warranty or representation to you that the Product does not infringe the intellectual property rights of any third party. All orders accepted shall be subject to the standard conditions of sale of allnex which are on the back of our invoice. In accepting the Product you, the customer acknowledge and agree: a.) The Product is or may be of a hazardous nature and that you, the customer, are responsible for the disposal of the container housing the Product in accordance with the requirements and regulations of the relevant supervising government. b.) The Product has a limited shelf life and must be stored strictly in accordance with the guidelines and specifications related to it. c.) Where the Details relate to Product tested by allnex, those Details are indicative only, regarding which there may be batch to batch variation. d.) allnex gives no warranty or representation as to the applicability for the particular use by you, the customer, of the Product and you the customer shall be responsible for ensuring that the Product is fit for your intended use. e.) allnex's liability for breach of any term, condition, guarantee or warranty (express or implied and concerning the information in this Document or the Product more generally) including any liability for direct or indirect consequential loss (including indirect loss of profits), is limited to the maximum extent permitted by law and, at allnex's election, to either replacing or repairing the goods or paying the cost of replacing or repairing the goods, or in the case of services, supplying the services again.