

DESCRIPTION

XPRESS ISO is a high performance insulating base sheet panel composed of SBS modified bitumen membrane with a non-woven polyester reinforcement, factory-laminated on a high density mineral wool (stone wool) support panel and on a polyisocyanurate insulation board (**SOPRA-ISO**). The surface is covered with a thermofusible plastic film.

INSTALLATION

BITUMEN

XPRESS ISO panel is installed in a bed of hot bitumen applied with a mop.

ADHESIVE

XPRESS ISO panel is adhered with **DUOTACK** adhesives.

MECHANICALLY FASTENED

XPRESS ISO panel is mechanically fastened to steel deck with **SOPREMA** screws and plates for membranes.

Mechanical fasteners must be installed on the distinctive line of the membrane side selvedge. On a steel deck, fasteners must be installed on the steel deck top flanges. Install membranes perpendicular to the steel deck ribs.

For more details about the required number of adhesive or mechanical fasteners, consult the Wind Uplift Resistance Testing reports according to Canadian standard CSA A123.21.

DUO SELVEDGE

Over the entire width of DUO SELVEDGE, 60 % of the surface is self-adhesive, which protects components under the base sheet. The remaining surface of the selvedge (40 %) is covered by a thermofusible plastic film to seal overlap by heat-welding with a propane torch or with the **SOPRAMATIC** automatic hot-air welder.

FOR COMPLETE INFORMATION ON PRODUCT INSTALLATION, PLEASE CONSULT YOUR ALLNEX REPRESENTATIVE.

PACKAGING

Specifications	XPRESS ISO
Total thickness (Membrane & boards)	89.9 mm (75mm Polyiso) 114.9 mm (100 mm Polyiso)
Reinforcement of the membrane	Non-woven polyester
Support panel dimensions (HD mineral wool)	0.91 X 2.13
Insulation panel dimensions (Polyiso)	0.91 X 2.13
Total weight	6.85 kg/m ²
Selvedge width	90 mm
Surface	Thermofusible plastic film
Underface	Polyisocyanurate

(All values are nominal)

PROPERTIES

Properties	Standards	MEMBRANE
Membrane Thickness	-	2.2 mm
Breaking Strength, MD/XD	CAN/CGSB-37.56-M, 9 th draft	17.0 / 12.5 kN/m
Ultimate Elongation, MD/XD	CAN/CGSB-37.56-M, 9 th draft	60 / 65%
Tear Strength	ASTM D5601	60 N
Cold Bending -Initial -90 days at 70°C	CAN/CGSB-37.56-M, 9 th draft	-30 °C -30 °C

(All values are nominal)

Properties	Standards	HD MINERAL WOOL (STONE WOOL)
Board thickness	-	12.7 mm
Thermal Resistance R-Value (RSI)	ASTM C518(C177)	0.70 m ² K/W
Reaction to fire	ASTM E84	Smoke spread: 0 Smoke develop index: 0
Water Absorption	ASTM C209	<1%
Compressive Strength	ASTM C165	75 kPa
Dimensional stability: Linear Shrinkage	ASTM C356	1.1% @ 650°C

(All values are nominal)

Properties	Standards	POLYISOCYANURATE INSULATION BOARD (SOPRA-ISO)
Board Thickness	-	75mm 100mm
Compressive Strength	ASTM D 1621	138 kPa
Density	ASTM D 1622	32 kg/m ³
Linear Dimensional Stability	ASTM D 2126	<2.0%
Water Absorption	ASTM C 209 ASTM D 2842	<1.0% <3.5%
Flame Spread*	ASTM E 84	40 – 60
Tensile Strength	ASTM D 1623	35 kPa

(All values are nominal)

STORAGE AND HANDLING

XPRESS ISO insulating base sheet panels must be stored on a flat substrate and sheltered from inclement weather. If the products are stored outdoors, cover them with an opaque protection cover.

Date: July 2018

Replaces: New



Allnex Construction Products, a Division of Allnex New Zealand Ltd

Auckland - 14 Industry Road Penrose phone: 095836544. Hamilton - 18 Somerset Street Frankton phone: 07-847-8658

Wellington - 19A Jamaica Drive Grenada North phone: 04-240-0305. Christchurch - 112 Carlyle Street Sydenham phone: 03-366-6802

Customer Service: 0508-882-288 cs.constructionnz@allnex.com

www.allnexconstruction.com

DISCLAIMER: This information appearing in this Document (**Details**) concerning the product which is the subject of the Document (**Product**) is either based on present technical knowledge and tests done by allnex or tests done by, and data supplied from third parties including you, the customer. Since the actual use by you and by others of the Product is beyond the control of allnex, no warranty or representation, express or implied is made by allnex regarding the suitability for such use, nor does allnex accept any liability arising out of the use by you of other products or materials, whether third party or not, that may be referred to in this Document. allnex recommends that you carry out your own tests as to the suitability of the Product for your purpose, regarding which you accept full responsibility. In addition, if any of the Details appearing in the Document are based upon tests done by, and/or data supplied by any third party, allnex provides no warranties or representations in connection with those Details and you, the customer waives any right you may have against allnex in connection with the accuracy, completeness or otherwise of the Details. The information in this Document is not to be construed as absolutely complete or accurate since additional information may be necessary or desirable when particular or exceptional conditions or circumstances exist or because of applicable laws or government regulations affecting use of the Product. allnex does not provide any warranty or representation to you that the Product does not infringe the intellectual property rights of any third party. All orders accepted shall be subject to the standard conditions of sale of allnex which are on the back of our invoice. In accepting the Product you, the customer acknowledge and agree: **a.)** The Product is or may be of a hazardous nature and that you, the customer, are responsible for the disposal of the container housing the Product in accordance with the requirements and regulations of the relevant supervising government. **b.)** The Product has a limited shelf life and must be stored strictly in accordance with the guidelines and specifications related to it. **c.)** Where the Details relate to Product tested by allnex, those Details are indicative only, regarding which there may be batch to batch variation. **d.)** allnex gives no warranty or representation as to the applicability for the particular use by you, the customer, of the Product and you the customer shall be responsible for ensuring that the Product is fit for your intended use. **e.)** allnex's liability for breach of any term, condition, guarantee or warranty (express or implied and concerning the information in this Document or the Product more generally) including any liability for direct or indirect consequential loss (including indirect loss of profits), is limited to the maximum extent permitted by law and, at allnex's election, to either replacing or repairing the goods or paying the cost of replacing or repairing the goods, or in the case of services, supplying the services again.